

The USB 2.0 wireless card supporting 802.11b/g (2.4GHz) radio operation. It provides high-speed wireless connection with data rate up to 108Mbps. The shirking dimension, light weight & lower power consumption design can easily integrate into a wide range of OEM/ODM device

EUB-362(EXT) has high power and high sensitivity. Further, it provides an external antenna which can easily advance your distance and performance more flexible.



To protect your wireless connectivity, the high-speed wireless USB adapter can encrypt all wireless transmissions through 64/128/152-bit WEP data encryption and also supports WPA. With the high-speed wireless USB adapter, you will experience the best wireless connectivity available.

Features	Benefits
High Speed Data Rate up to 108Mbps in Super G mode	Capable of handling heavy data payloads such as MPEG video streaming.
High Output Power up to 23 dBm	Excellent output power spreads the operation distance
Advanced Encryption Standard (AES), Temporal Key Integrity Protocol (TKIP) and Wired Equivalent Private (WEP)	Powerful data security.
IEEE802.1x Client Support	Enhances authentication and security.
Support for 802.11e standard	Wireless Multimedia Enhancements Quality of Service support (QoS)
Advanced Power Management	Low power consumption in power saving mode up to 98%.
Support eXtended Range technology	eXtended Range technology give Wi-Fi products twice the range of existing designs
External (changeable) Antenna	Changeable Antenna provides users more flexible to select other antennas

*** Subject to change without prior notice

Technical Specifications

Data Rates

802.11g: 6, 9, 12, 18, 24, 36, 48, 54, and
Up to 108 Mbps

802.11b: 1, 2, 5.5 and 11Mbps

Standards / Compliance

IEEE802.11, IEEE802.11g, IEEE802.11b, draft IEEE 802.11e,
and i standards, IEEE802.1x

Regulation Certifications

FCC Part 15, ETSI 300/328/CE

Operating Voltage

5 V ± 0.25V

Status LEDs

RF link activity

Drivers

Windows 2000/XP

RF INFORMATION

Frequency Band

U.S., Europe and Japan product covering 2.4 to 2.484
GHz, programmable for different country regulations

Media Access Protocol

Carrier Sense Multiple Access with Collision Avoidance
(CSMA/CA)

Modulation Technology

802.11g: OFDM (64-QAM, 16-QAM, QPSK, BPSK)

802.11b: DSSS (DBPSK, DQPSK, CCK)

Operating Channels

11 for North America, 14 for Japan, 13 for Europe, 2 for
Spain, 4 for France

Receive Sensitivity (Typical)

- 2.412~2.472G(IEEE802.11g)

6Mbps@ -91dBm;

54Mbps@ -76dBm

- 2.412~2.472G(IEEE802.11b)

11Mbps@ -91dBm;

1Mbps@ -96dBm

Available transmit power

FCC (Typical)

- 2.412~2.472G(IEEE802.11g)

22 dBm @ 6 ~ 24 Mbps

21 dBm @ 36 Mbps

20 dBm @ 48 Mbps

19 dBm @ 54 Mbps

- 2.412~2.472G(IEEE802.11b)

22 dBm @1~11Mbps

ETSI (Typical)

- 2.412~2.472G(IEEE802.11g)

20 dBm @ 6 ~ 24 Mbps

20 dBm @ 36 Mbps

20 dBm @ 48 Mbps

19 dBm @ 54 Mbps

- 2.412~2.472G(IEEE802.11b)

20 dBm @1~11Mbps

Antenna

Dipole antenna (2dBi detachable antenna)

NETWORKING

Topology

Ad-Hoc, Infrastructure

Security

IEEE802.1x support for LEAP/PEAP

WPA – Wi-Fi Protected Access (AES, 64,128,152-WEP with
shared-key authentication)

PHYSICAL

Form Factor

USB 2.0 / 1.1

Dimensions (LxWxH)

75.2(L) mm x 53.9(W) mm x 14(H) mm

Weight

40 g/ 1.5oz

ENVIRONMENTAL

Temperature Range

Operating: -0°C to 55°C

Storage: -20°C to 75°C

Humidity (non-condensing)

5%~95% Typical

Package Contents

One CD-ROM with User's Manual and Drivers

One USB dongle

One Antenna (2dBi)

*** Subject to change without prior notice